# Suction cup with connection
# VASB-125-3/8-PUR-B

Part number: 1396067





## Data sheet

| Feature | Value |
|---|---|
| Height compensator for suction cup | 25 mm |
| Nominal size | 7 mm |
| Suction cup diameter | 125 mm |
| Suction cup volume | 307 cm³ |
| Effective suction diameter | 101.8 mm |
| Position of connection | On top |
| Mounting position | Any |
| Suction cup shape | Round protective bellows 1.5-fold |
| Operating pressure | -0.095 MPa...0 MPa<br>-0.95 bar...0 bar<br>-13.775 psi...0 psi |
| Nominal operating pressure | -0.07 MPa<br>-0.7 bar<br>-10.15 psi |
| Operating medium | Atmospheric air based on ISO 8573-1:2010 [7:-:-] |
| Corrosion resistance class CRC | 2 - Moderate corrosion stress |
| LABS (PWIS) conformity | VDMA24364-A1-L |
| Ambient temperature | -20 °C...60 °C |
| Holding force at nominal operating pressure | 570 N |
| Product weight | 294 g |
| Type of mounting | Via vacuum port |
| Vacuum connection | G3/8 |
| Colour | Blue |
| Shore hardness | 60 +/-5 |
| Material screwed plug | Die-cast zinc |
| Note on materials | RoHS compliant |
| Material suction cup | PUR |