

# Multiple distributor QST3-10-8

Part number: 153205

**FESTO**



## Data sheet

| Feature                                       | Value                                                                 |
|-----------------------------------------------|-----------------------------------------------------------------------|
| Size                                          | Standard                                                              |
| Nominal size                                  | 4.9 mm                                                                |
| Tubing insertion depth                        | 18 mm<br>20 mm                                                        |
| Note on the tubing insertion depth            | Ø8 depth 18 mm<br>Ø10 depth 20 mm                                     |
| Mounting position                             | Any                                                                   |
| Design                                        | Push-pull principle                                                   |
| Size of pack                                  | 1                                                                     |
| Operating pressure complete temperature range | -0.095 MPa...0.6 MPa<br>-0.95 bar...6 bar<br>-13.775 psi...87 psi     |
| Temperature-dependent operating pressure      | -0.095 MPa...1.4 MPa<br>-0.95 bar...14 bar<br>-13.775 psi...203 psi   |
| Note on operating pressure                    | Water: max. 0.6 MPa at 0 - 50 °C                                      |
| Maritime classification                       | See certificate                                                       |
| Operating medium                              | Compressed air to ISO 8573-1:2010 [7:-:-]<br>Water (liquid, ice-free) |
| Note on operating and pilot medium            | Lubricated operation possible                                         |
| Corrosion resistance class CRC                | 1 - Low corrosion stress                                              |
| LABS (PWIS) conformity                        | VDMA24364-B1/B2-L                                                     |
| Ambient temperature                           | -10 °C...80 °C                                                        |
| Product weight                                | 33 g                                                                  |
| Number of outputs                             | 4                                                                     |
| Number of supply lines                        | 1                                                                     |
| Pneumatic connection, port 1                  | For tubing outer diameter of 10 mm                                    |
| Pneumatic connection, port 2                  | For tubing outside diameter of 8 mm                                   |
| Colour of release ring                        | Blue                                                                  |
| Note on materials                             | RoHS compliant                                                        |
| Material housing                              | PBT                                                                   |
| Material release ring                         | POM                                                                   |
| Material tubing seal                          | NBR                                                                   |

| Feature                         | Value                      |
|---------------------------------|----------------------------|
| Material tubing clamp component | High-alloy stainless steel |