# Filter combination
# LFMBA-1/4-D-MINI

Part number: 162659




## Data sheet

| Feature | Value |
|---|---|
| Size | Mini |
| Series | D |
| Mounting position | Vertical +/-5° |
| Grade of filtration | 0.01 µm |
| Filter efficiency | 99.9999 % |
| Condensate drain | Manual, rotating |
| Design | Fibre filter |
| Max. condensate volume | 22 ml |
| Bowl guard | Metal bowl guard |
| Operating pressure | 1 bar...16 bar |
| Operating medium | Compressed air to ISO 8573-1:2010 [6:8:4]<br>Inert gas |
| LABS (PWIS) conformity | VDMA24364-B1/B2-L |
| Air purity class at output | Compressed air to ISO 8573-1:2010 [1:7:2]<br>Inert gas |
| Media temperature | 1.5 °C...60 °C |
| Residual oil content | 0.01 mg/m³ |
| Ambient temperature | -10 °C...60 °C |
| Product weight | 500 g |
| Type of mounting | Inline installation<br>With accessories |
| Pneumatic connection, port 1 | G1/4 |
| Pneumatic connection, port 2 | G1/4 |
| Note on materials | RoHS compliant |
| Material filter | Borosilicate fibre |
| Material housing | Die-cast zinc |
| Material bowl | Makrolon® |