


# On/off valve HEL-1/2-D-MIDI

Part number: 165080

FESTO



## Data sheet

| Feature                                               | Value                                                                                      |
|-------------------------------------------------------|--------------------------------------------------------------------------------------------|
| Exhaust-air function                                  | Can be throttled                                                                           |
| Type of actuation                                     | Pneumatic                                                                                  |
| Sealing principle                                     | Soft                                                                                       |
| Mounting position                                     | Any                                                                                        |
| Manual override                                       | None                                                                                       |
| Design                                                | Piston gate valve                                                                          |
| Type of reset                                         | Mechanical spring                                                                          |
| Type of piloting                                      | Direct                                                                                     |
| Flow direction                                        | Non-reversible                                                                             |
| Valve function                                        | 2/2-way, single solenoid, closed                                                           |
| Operating pressure                                    | 0.3 MPa...1.6 MPa<br>3 bar...16 bar                                                        |
| b value                                               | 0.37                                                                                       |
| C value                                               | 19.8 l/sbar                                                                                |
| Standard nominal flow rate (standardised to DIN 1343) | 3600 l/min                                                                                 |
| Operating medium                                      | Compressed air to ISO 8573-1:2010 [7:4:4]<br>Inert gas                                     |
| Note on operating and pilot medium                    | Lubricated operation possible (in which case lubricated operation will always be required) |
| Corrosion resistance class CRC                        | 2 - Moderate corrosion stress                                                              |
| LABS (PWIS) conformity                                | VDMA24364-B1/B2-L                                                                          |
| Air purity class at output                            | Compressed air to ISO 8573-1:2010 [7:4:4]<br>Inert gas                                     |
| Media temperature                                     | -10 °C...60 °C                                                                             |
| Ambient temperature                                   | -10 °C...60 °C                                                                             |
| Product weight                                        | 270 g                                                                                      |
| Type of mounting                                      | Inline installation                                                                        |
| Pneumatic connection, port 1                          | G1/2                                                                                       |
| Pneumatic connection, port 2                          | G1/2                                                                                       |
| Note on materials                                     | RoHS compliant                                                                             |
| Material seals                                        | NBR                                                                                        |

| Feature          | Value              |
|------------------|--------------------|
| Material housing | Die-cast aluminium |