


# Service unit combination LFR-1/2-D-MIDI-KA-A

Part number: 185716

**FESTO**



## Data sheet

| Feature                                               | Value                                                        |
|-------------------------------------------------------|--------------------------------------------------------------|
| Size                                                  | Midi                                                         |
| Series                                                | D                                                            |
| Actuator lock                                         | Rotary knob with detent                                      |
| Mounting position                                     | Vertical +/- 5°                                              |
| Grade of filtration                                   | 40 µm                                                        |
| Condensate drain                                      | Fully automatic                                              |
| Design                                                | Branching module<br>Filter regulator with pressure gauge     |
| Max. condensate volume                                | 43 cm <sup>3</sup>                                           |
| Bowl guard                                            | Metal bowl guard                                             |
| Pressure gauge (ANALOG) or Pressure display (DIGITAL) | With pressure gauge                                          |
| Operating pressure                                    | 0.2 MPa...1.2 MPa<br>2 bar...12 bar<br>29 psi...174 psi      |
| Pressure regulation range                             | 0.05 MPa...1.2 MPa<br>0.5 bar...12 bar<br>7.25 psi...174 psi |
| Max. pressure hysteresis                              | 0.02 MPa<br>0.2 bar<br>2.9 psi                               |
| Standard nominal flow rate (standardised to DIN 1343) | 3050 l/min                                                   |
| Operating medium                                      | Compressed air to ISO 8573-1:2010 [-:-:-]<br>Inert gas       |
| Corrosion resistance class CRC                        | 2 - Moderate corrosion stress                                |
| LABS (PWIS) conformity                                | VDMA24364-B1/B2-L                                            |
| Air purity class at output                            | Compressed air to ISO 8573-1:2010 [7:8:4]<br>Inert gas       |
| Media temperature                                     | -10 °C...60 °C                                               |
| Ambient temperature                                   | -10 °C...60 °C                                               |
| Product weight                                        | 1800 g                                                       |
| Type of mounting                                      | Either:<br>Inline installation<br>With accessories           |
| Pneumatic connection, port 1                          | G1/2                                                         |

| Feature                      | Value         |
|------------------------------|---------------|
| Pneumatic connection, port 2 | G1/2          |
| Material housing             | Die-cast zinc |
| Material bowl                | Makrolon®     |