

# Spiral plastic tubing PUN-6X1-S-6-SW

Part number: 197607

**FESTO**



## Data sheet

| Feature                                  | Value                                                                                                          |
|------------------------------------------|----------------------------------------------------------------------------------------------------------------|
| Working length                           | 6 m                                                                                                            |
| Outside diameter                         | 6 mm                                                                                                           |
| Block length                             | 1.214 m                                                                                                        |
| Inside diameter                          | 4 mm                                                                                                           |
| Winding diameter                         | 46 mm                                                                                                          |
| Number of turns                          | 168                                                                                                            |
| Temperature-dependent operating pressure | -0.095 MPa...1 MPa<br>-0.95 bar...10 bar<br>-13.775 psi...145 psi                                              |
| Approval                                 | German Technical Control Board (TÜV)                                                                           |
| Certificate issuing authority            | B 013277 0527 00                                                                                               |
| Operating medium                         | Compressed air to ISO 8573-1:2010 [7:-:-]                                                                      |
| LABS (PWIS) conformity                   | VDMA24364-B2-L                                                                                                 |
| Ambient temperature                      | -35 °C...60 °C                                                                                                 |
| Product weight                           | 350 g                                                                                                          |
| Pneumatic connection                     | For push-in connector O.D. 6 mm<br>For barbed fitting I.D. 4 mm with union nut<br>For barbed fitting I.D. 4 mm |
| Colour                                   | Black                                                                                                          |
| Shore hardness                           | D 52 +/-3                                                                                                      |
| Material tubing                          | TPE-U(PU)                                                                                                      |