

Pressure sensor SDE5-

Part number: 529027

FESTO



Data sheet

Feature	Value
Approval	RCM c UL us - Recognised (Oil)
CE mark (see declaration of conformity)	To EU EMC Directive In accordance with EU RoHS Directive
UKCA marking (see declaration of conformity)	To UK instructions for EMC To UK RoHS instructions
Note on materials	RoHS compliant
Measured variable	Differential pressure Relative pressure
Measurement method	Piezoresistive pressure sensor
Start value for pressure measuring range	-0.1 MPa -1 bar -14.5 psi
End value for pressure measuring range	1 MPa 10 bar 145 psi
Overload pressure	0.5 MPa...1.5 MPa 5 bar...15 bar 72.5 psi...217.5 psi
Operating medium	Compressed air to ISO 8573-1:2010 [7:4:4]
Note on operating and pilot medium	Lubricated operation possible
Media temperature	0 °C...50 °C
Ambient temperature	0 °C...50 °C
Accuracy in ± % FS	0.5 %FS...3 %FS
Repetition accuracy in ± %FS	0.3 %FS
Temperature coefficient in ± %FS/K	0.05 %FS/K
Long-term drift	±0.5 % FS max.
Switching output	NPN PNP
Switching function	Window comparator Freely programmable Threshold value with fixed hysteresis Threshold value with variable hysteresis
Switching element function	N/C contact N/O contact Switchable

Feature	Value
Hysteresis in $\pm$ %FS	1 %FS...99 %FS
Switch-on time	2 ms
Switch-off time	2 ms
Max. output current	5 mA...100 mA
Voltage drop	1.8 V
Analogue output	0 - 10 V
Output characteristic curve start value	0 V
Output characteristic curve end value	10 V
Accuracy analogue output in $\pm$ %FS	3 %FS
Linearity error in $\pm$ %FS	0.3 %FS
Rise time	5 ms
Min. load resistance voltage output	20 kOhm
Short circuit current rating	Yes
Overload protection	Yes
Operational voltage range DC	15 V...30 V
Permissible voltage fluctuations	+/-10%
Reverse polarity protection	For all electrical connections
Electrical connection 1, connection type	Cable Plug
Electrical connection 1, connector system	M8x1, A-coded, to EN 61076-2-104 Open end
Electrical connection 1, number of connections/cores	3
Electrical connection 1, type of mounting	Snap-locking Screw-type lock Not rotatable
Electrical connection 1, compatible type of mounting	Compatible with latching lock Compatible with rotatable screw-type lock
Cable length	2.5 m
Type of mounting	With accessories
Mounting position	Any
Pneumatic connection	QS-4 QS-6 QS-5/32 QS-1/4
Product weight	19 g...47 g
Material housing	Reinforced PA Reinforced POM
Material in contact with the medium	Reinforced POM
Material sealing ring	Fluoro rubber NBR
Ready status indication	Green LED
Switching status indication	Yellow LED
Setting options	Teach-in
Setting range threshold value	0 %...100 %
Degree of protection	IP40
Corrosion resistance class CRC	2 - Moderate corrosion stress
LABS (PWIS) conformity	VDMA24364-B1/B2-L
Cleanroom suitability, measured according to ISO 14644-14	Class 4 according to ISO 14644-1